



-RT-RX-

-1100-1400-1600-



-R series-



COSMO

IS EAGER TO INTRODUCE THE NEW LINE OF DOUBLE DISC SPREADERS ALLOWING TO REACH A

24 METERS SPREADING WIDTH AND WITH HOPPER CAPACITY FROM 1200 KG TO 1800 KG. THESE SPREADERS

LINE COMES STANDARD WITH A HYDRAULIC OPENING SYSTEM, PERMITTING A REGULATION FROM THE TRACTOR CABIN.

THE TWO SPREADING DISCS ARE STANDARD IN STAINLESS STEEL, THE LEVERAGE SYSTEM AND ALL THE

COMPONENTS OF THE RX LINE ARE ALL IN STAINLESS STEEL TOO WHILE FOR THE RT LINE THEY ARE IN PAINTED STEEL.



THE HOPPER INCLUDES A REMOVABLE FILTERING GRIND,

USEFUL TO AVOID ALSO THE USER CONTACT WITH TWO STANDARD SLOW PACE AGITATORS IN THE BOTTOM. THE AGITATORS GUARANTEE A EVEN FERTILIZER SPREADING.

THE STANDARD INCLUDED PTO SHAFT, IS ENDOWED WITH A PAWLS CLUTCH THAT PERFORMS IN CASE OF POWER PEAKS WHICH COULD DAMAGE THE PTO ITSELF OR THE GEARS.

THE DOUBLE LIFT ARM PINS PERMIT TO HITCH THE MACHINE TO II OR III CATEGORY TRACTOR 3-POINTS HITCHES.

THE STAINLESS STEEL FIN OF THE DISCS ARE AVAILABLE IN DIFFERENT LENGTHS IN ORDER TO MEET DIFFERENT SPREADING WIDTHS' REQUESTS.

MODELS	RT 1100	RT 1400	RX 1100	RX 1400	RX 1600
CAPACITY(L)	1100	1400	1100	1400	1600
SPREADING WIDTH (M)	12/24	12/24	12/24	12/24	12/24
WEIGHT(KG)	310	323	335	350	350
DISC	2inox	2inox	2inox	2inox	2inox
EXIT LEVER	Mechanical/Hydraulic	Mechanical/Hydraulic	Mechanical/Hydraulic(nox)	Mechanical/Hydraulic(nox)	Mechanical/Hydraulic(nox)
DOSE ADJUSTEMENT	Manual/Electronic	Manual/Electronic	Manual/Electronic	Manual/Electronic	Manuale/Elettronica
SPREADING WIDTH	180°/90° right or left	180°/90° right or left	180°/90° right or left	180°/90° right or left	180°/90° right or left
FILTRATING GRINDS	Standard	Standard	Standard	Standard	Standard
WIDTH (CM)	130	130	130	130	130
LENGTH (CM)	230	230	230	230	230
HEIGHT (CM)	105	105	105	105	105

